



Huahuineng Lighting Technology Co., Ltd

Add: Building 4-6, Jiatiangang Industrial Park, Huangtian, Xixiang, Baoan district, Shenzhen, Guangdong, China



Tel: 86-755-29702082

Fax: 86-755-26068103

Web: www.szhhl.com

Email: jikangtony@gmail.com

Model No.	Photo	Technical Specification	Certifications	Packaging	Price(FOB shenzhen) USD
LED tunnel light HD-SDD96		Number of LED: 96pcs * 1W (Equal to 250W traditional HPS) Light color: Natural white Working voltage: AC100-240 Tem color: 5500-6200K Ambient tem: -40°C-50°C Relative humidity: 10%-95% IP rating: IP65 Power factor: >0.97 Power efficiency: >90% Service life: >50,000 hours	CE & ROHS	Product Size: 348*324*175(MM) Net weight: 10KG Gross weight: 11.2KG 1 PC/CTN CTN Size: 440*430*245(MM)	Seoul (CREE Chip) \$605.27 Huayang(Bridgelux Chip) \$563.08
LED tunnel light HD-SDD128		Number of LED: 128pcs * 1W (Equal to 400W traditional HPS) Light color: Natural white Working voltage: AC100-240 Tem color: 5500-6200K Ambient tem: -40°C-50°C Relative humidity: 10%-95% IP rating: IP65 Power factor: >0.97 Power efficiency: >90% Service life: >50,000 hours	CE & ROHS	Product Size: 348*324*175(MM) Net weight: 10KG Gross weight: 11.2KG 1 PC/CTN CTN Size: 440*430*245(MM)	Seoul (CREE Chip) \$713.20 Huayang(Bridgelux Chip) \$619.35



<p>LED street light HD-LD96</p>	 <p>HONL HONGNAN LED LAMP CE RoHS</p>	<p>Number of LED: 96pcs * 1W (Equal to 250W traditional HPS) Lighr color: Natural white Working voltage: AC100-240 Tem color: 5500-6200K Ambient tem: -40°C-50°C Relative humidity: 10%-95% IP rating: IP65 Power factor: >0.97 Power efficiency: >90% Service life: >50,000 hours</p>	<p>CE & ROHS</p>	<p>Product Size: 625*365*130(MM) Net weight: 11.8KG Gross weight: 13.6KG 1 PC/Carton Carton Size: 775*450*200(MM)</p>	<p>Seoul (CREE Chip) \$605.27 Huayang(Bridgelux Chip) \$563.08</p>
<p>LED street light HD-LD128</p>	 <p>HONL HONGNAN LED LAMP CE RoHS</p>	<p>Number of LED: 128pcs * 1W (Equal to 400W traditional HPS) Lighr color: Natural white Working voltage: AC100-240 Tem color: 5500-6200K Ambient tem: -40°C-50°C Relative humidity: 10%-95% IP rating: IP65 Power factor: >0.97 Power efficiency: >90% Service life: >50,000 hours</p>	<p>CE & ROHS</p>	<p>Product Size: 625*365*130(MM) Net weight: 11.8KG Gross weight: 13.6KG 1 PC/Carton Carton Size: 775*450*200(MM)</p>	<p>Seoul (CREE Chip) \$713.20 Huayang(Bridgelux Chip) \$619.35</p>
<p>Features</p>	<ol style="list-style-type: none"> 1. Patented heat dissipation structure(patent No ZL200720119365.1) make the working tempreature of our products 8.24 degree lower than other suppliers, which means the lifespan is 2 to 3 years longer than other suppliers' product; 2. Cooperate with professional power source manufacturer, the power source use for our lamps are very high quality(power factor>0.97, power effency>90%),more than 50000h service time of the power ensure the service time of the whole lamp. 3. With a breathing system, dust&waterproof and self-cleaning, meeting IP65 rating. 4. Built-in heat radiator, beautiful appearance with many national patents. 				

Packaging pictures





Remark: Currency rate between US Dollar and RMB: 6.82



Item No.	Photo	LED Brand	Technical Parameters	Certified	Unit price (FOB Shenzhen)
LED tube HD-T01		<p>EVERLIGHT (from Taiwan)</p>	<ul style="list-style-type: none"> * Power: 8 W * LED Qty: 120 PCS SMD3528 * Equal to common fluorescent lamp: 20W * Working Voltage: 85-265 V * Color Temperature: Natural white 6200K * Base Type: T8 / 600 mm * Luminous Flux: <ul style="list-style-type: none"> Natural white: 750LM(transparent) * Working Temperature: -30°C ~+ 55°C * Viewing Angle: 120deg. * Lifespan: ≥ 50,000 hrs * Color Rendering Index: Ra>70% * Power Factor: 0.97 * Product Dimension: Φ30*600 mm * Material: Aluminum shell + PC 	<p>CE,RoHS</p>	<p>US\$17.50 (transparent)</p> <p>US\$17.80 (frosted)</p>
LED tube HD-T02		<p>EVERLIGHT (from Taiwan)</p>	<ul style="list-style-type: none"> * Power: 9 W * LED Qty: 144 PCS SMD3528 * Equal to common fluorescent lamp: 20W * Working Voltage: 85-265 V * Color Temperature: Natural white 6200K Warm White 3000K * Base Type: T8 / 600 mm * Luminous Flux: <ul style="list-style-type: none"> Natural white: 770LM(frosted) Warm white: 570LM (frosted) * Working Temperature: -30°C ~+ 55°C * Viewing Angle: 120deg. * Lifespan: ≥ 50,000 hrs * Color Rendering Index: Ra>70% * Power Factor: 0.97 * Product Dimension: Φ30*600 mm * Material: Aluminum shell + PC 	<p>CE,RoHS</p>	<p>US\$18.97 (transparent)</p> <p>US\$19.27 (frosted)</p>

<p>LED tube HD-T03</p>	 <p>HONL 華 慧 能 照 明</p> <p>CE</p>	<p>EVERLIGHT (from Taiwan)</p>	<ul style="list-style-type: none"> * Power: 15 W * LED Qty: 240 PCS SMD3528 * Equal to common fluorescent lamp: 40W * Working Voltage: 85-265 V * Color Temperature: Natural white 6200K Warm White 3000K * Base Type: T8 / 1200 mm * Luminous Flux: <ul style="list-style-type: none"> Natural white: 1450LM(transparent) 1260LM (frosted) Warm white: 950LM(frosted) * Working Temperature: -30°C ~+ 55°C * Viewing Angle: 120deg. * Lifespan: ≥50,000 hrs * Color Rendering Index: Ra>70% * Power Factor: 0.97 * Product Dimension: Φ30*1200 mm * Material: Aluminum shell + PC 	<p>CE,RoHS</p>	<p>US\$28.35 (transparent)</p> <p>US\$28.65 (frosted)</p>
<p>LED tube HD-T05</p>	 <p>HONL 華 慧 能 照 明</p> <p>CE</p>	<p>EVERLIGHT (from Taiwan)</p>	<ul style="list-style-type: none"> * Power : 18 W * LED Qty : 276 PCS SMD3528 * Equal to common fluorescent lamp: 40W * Working Voltage: 85-265 V * Color Temperature : Natural white 6200K Warm White 3000K * Base Type: T8 / 1200 mm * Luminous Flux : <ul style="list-style-type: none"> Natural white : 1700LM (transparent) 1430LM(frosted) Warm white : 1080LM (frosted) * Working Temperature : -30°C ~+ 55°C * Viewing Angle: 120deg. * Lifespan: ≥50,000 hrs * Color Rendering Index : Ra>70% * Power Factor : 0.97 * Product Dimension : Φ30*1200 mm * Material: Aluminum shell + PC 	<p>CE,RoHS</p>	<p>US\$30.50 (transparent)</p> <p>US\$30.80 (frosted)</p>
<p>Remark</p>	<p>Currency rate between US Dollar and RMB: 6.82</p>				

Features

1. There is a layer of high-efficiency double-faced liquid bond between the Aluminum base and heat radiator, which the the heat dissipation is better.
- 2.The power efficiency of our LED tubes is very high, about 97%, so the actual power the tubes consume is almost the same as the rated power.
- 3.Built-in power supply, and there is a layer of clapboard between the power supply and aluminum base, which can reduce the influence to the LEDs arosed by heat dissipation of the power supply.
4. Both ends of our LED tubes locked by screw and can be opened easily, convenient to maintenance

Item No.	Photo	LED Brand	Technical Parameters	Certified	Unit price (FOB Shenzhen)
LED tube HD-T01		<p>EVERLIGHT (from Taiwan)</p>	<ul style="list-style-type: none"> * Power: 8 W * LED Qty: 120 PCS SMD3528 * Equal to common fluorescent lamp: 20W * Working Voltage: 85-265 V * Color Temperature: Natural white 6200K * Base Type: T8 / 600 mm * Luminous Flux: <ul style="list-style-type: none"> Natural white: 750LM(Clear) * Working Temperature: -30℃ ~+ 55℃ * Viewing Angle: 120deg. * Lifespan: ≥50,000 hrs * Color Rendering Index: Ra>70% * Power Factor: 0.97 * Product Dimension :Φ30*600 mm * Material: Aluminum shell + PC 	CE,RoHS	<p>US\$17.50 (clear)</p> <p>The diameter of our LED tubes is 30mm, which is better for heat dissipation than diameter 26mm.</p>
LED tube HD-T02		<p>EVERLIGHT (from Taiwan)</p>	<ul style="list-style-type: none"> * Power: 9 W * LED Qty: 144 PCS SMD3528 * Equal to common fluorescent lamp: 20W * Working Voltage: 85-265 V * Color Temperature: Natural white 6200K Warm White 3000K * Base Type: T8 / 600 mm * Luminous Flux: <ul style="list-style-type: none"> Natural white: 800LM (milky) Warm white: 600LM (milky) * Working Temperature: -30℃ ~+ 55℃ * Viewing Angle: 120deg. * Lifespan: ≥50,000 hrs * Color Rendering Index: Ra>70% * Power Factor: 0.97 * Product Dimension :Φ30*600 mm * Material: Aluminum shell + PC 	CE,RoHS	<p>US\$19.27 (Milky)</p>

<p>LED tube HD-T03</p>		<p>EVERLIGHT (from Taiwan)</p>	<ul style="list-style-type: none"> * Power: 15 W * LED Qty: 240 PCS SMD3528 * Equal to common fluorescent lamp: 40W * Working Voltage: 85-265 V * Color Temperature: Natural white 6200K Warm White 3000K * Base Type: T8 / 1200 mm * Luminous Flux: <ul style="list-style-type: none"> Natural white: 1450LM (clear) 1300LM (milky) Warm white: 1000LM (milky) * Working Temperature: -30°C ~+ 55°C * Viewing Angle: 120deg. * Lifespan: ≥50,000 hrs * Color Rendering Index: Ra>70% * Power Factor: 0.97 * Product Dimension :Φ30*1200 mm * Material: Aluminum shell + PC 	<p>CE,RoHS</p>	<p>US\$28.15 (Clear) US\$28.45 (Milky)</p>
<p>LED tube HD-T05</p>		<p>EVERLIGHT (from Taiwan)</p>	<ul style="list-style-type: none"> * Power: 18 W * LED Qty: 276 PCS SMD3528 * Equal to common fluorescent lamp: 40W * Working Voltage: 85-265 V * Color Temperature: Natural white 6200K Warm White 3000K * Base Type: T8 / 1200 mm * Luminous Flux: <ul style="list-style-type: none"> Natural white: 1700LM (clear) 1450LM(milky) Warm white: 1100LM (milky) * Working Temperature: -30°C ~+ 55°C * Viewing Angle: 120deg. * Lifespan: ≥50,000 hrs * Color Rendering Index: Ra>70% * Power Factor : 0.97 * Product Dimension :Φ30*1200 mm * Material: Aluminum shell + PC 	<p>CE,RoHS</p>	<p>US\$30.50 (Clear) US\$30.80 (Milky)</p>
<p>Remark</p>	<p>Currency rate between US Dollar and RMB: 6.82</p>				

Features

1. There is a layer of high-efficiency double-faced liquid bond between the Aluminum base and heat radiator, which the the heat dissipation is better.
2. The power efficiency of our LED tubes is very high, about 97%, so the actual power the tubes consume is almost the same as the rated power.
3. Built-in power supply, and there is a layer of clapboard between the power supply and aluminum base, which can reduce the influence to the LEDs arosed by heat dissipation of the power supply.
4. Both ends of our LED tubes locked by screw and can be opened easily, convenient to maintenance.



Huahuineng Lighting Technology Co., Ltd

Add: Building 4-6, Jiatiangang Industrial Park, Huangtian, Xixiang, Baoan district, Shenzhen, Guangdong, China (Manufacturer)

Tel: 86-755-29702082

Fax: 86-755-26068103

Web: www.szhhl.com

Email: jikangtony@gmail.com

Item No.	Photo	Technical Parameters	Certified	Unit price (FOB Shenzhen)
LED Panel Light HD-PP004L		<ul style="list-style-type: none">* Power: 24 W* LED Qty: 336 PCS SMD 3528 LEDs* Working Voltage: DC 36V* Color Temperature: 2800-6500K* Luminous Flux: 1680-2400 Lm* Working Temperature: -30°C ~+ 55°C* Viewing Angle: 180 deg.* Lifespan: ≥50,000 hrs* Color Rendering Index: Ra>75%* Power Factor: ≥ 0.85* Product Dimension: 300 *300*12.5 mm* Material: Aluminum shell + other	CE,RoHS	US\$68.50
LED Panel Light HD-PP005L		<ul style="list-style-type: none">* Power: 48 W* LED Qty: 672 PCS SMD 3528 LEDs* Working Voltage: DC 36V* Color Temperature: 2800-6500K* Luminous Flux: 3360-4800 Lm* Working Temperature: -30°C ~+ 55°C* Viewing Angle: 180 deg.* Lifespan: ≥50,000 hrs* Color Rendering Index: Ra>75%* Power Factor: ≥ 0.85* Product Dimension: 600 *600*12.5 mm* Material: Aluminum shell + other	CE,RoHS	US\$150.50

<p>LED Panel Light HD-PP006L</p>		<ul style="list-style-type: none"> * Power: 48 W * LED Qty: 672 PCS 5MM SMD 3528 LEDs * Working Voltage: DC 36V * Color Temperature: 2800-6500K * Luminous Flux: 3360-4800 lm * Working Temperature: -30°C ~+ 55°C * Viewing Angle: 180 deg. * Lifespan: ≥50,000 hrs * Color Rendering Index: Ra>75% * Power Factor: ≥ 0.85 * Product Dimension: 1200 *300*12.5 mm * Material: Aluminum shell + other 	<p>CE,RoHS</p>	<p>US\$180.20</p>
--------------------------------------	---	--	----------------	--------------------------

Remark:

1.Currency rate between US Dollar and RMB: 6.80

Features

- 1) Saving energy, low power consumes, long lifespan, reduce lighting consumption cost.
- 2) Intelligent remote control, adjust the brightness by yourself, convenient to use.
- 3) User-friendly design, combined with the latest technology.
- 4) No radiation, no flicker, high brightness, offer pollution-free, high quality light source for you.
- 5) Three pole luminance wireless dimmer (Off-100%brightness-66%brightness-33%brightness).
- 6)Visible led light beads(HY-F-600L,HY-F-300L),Side lighting (HY-F-600S, HY-F-600X , HY-F-300S, HY-F-300X)) ;
- 7) Led style straw hat or 3528.

Application: It's widely applied in office building、 school、 supermarket、 exhibition hall、 recreation spot and so on.

1. Payment Terms: TT, 50% as deposite before production, balance before shipment.

2.Lead Time: It will depends on the orde quantity.

3.valid time: within one month