

### LJ-M36WIR



#### FEATURES:

- It could penetrate through the forest and camouflage net compared with other cameras which could not carry out this function..
- Little power consumption, and endurable for using, with the farthest radicalization distance, it is up to 200 meters
- It could widely used for the environment such as night, bad environment, and farther range control.
- Weather proof design, high die-cast aluminum construction, anti-shock, anti-corrosion, the protection grade IP66, with wiper function.
- 360° continuously rotation, the range upward angle up to 180°, no blind spot .
- 128 preset positions and with 6 cruising tracks
- The power supply AC24V.

#### SPECIFICATION:

<b>Model</b>	<b>LJ-M18WIR</b>	<b>LJ-M26WIR</b>	<b>LJ-M36WIR</b>
Image sensor	1/4 Exview HAD CCD		
Active pixels	752 (H) X582 (V)		
Synchronization	Synchronization		
Video output	1.0Vp-p at 75ohm		
White balance	Auto / Manual		
Scanning frequency	15.625KHz(H) 50Hz		
Horizontal resolution	480TVL		
S/N Ratio	> 50dB		
Electronic shutter	1/1~1/10,000s	1/1~1/10,000s	1/50~1/10,000s
Min. illumination	0.01Lux	0.01Lux	0.7Lux
Focal length	F=4.1~73.8mm	F=3.5~91mm	F=3.4~122.4mm
Zoom	Total 216X Optical 18X Digital 12X	Total 312X Optical 26X Digital 12X	Total 432X Optical 36X Digital 12X
Focal & Iris	Auto / Manual		
<b>PTZ :</b>			
Pan preset speed	100°/s		
Tilt preset speed	60°/s		
Pan Speed:	0°~80°/s		
Pan Range:	360° Continuously		
Tilt Speed:	0~60°/sec		
Tilt Range:	+90°~-90°		
Preset track:	128 presets,6 tracks		
Communication:	Multi-protocol, Baud rate from 2400Bps to 19200Bps for optional, RS485 control		
Weight:	7 Kg		
Operating Temperature:	-35°C to +55°C (w/ Housing)		
Shock:	Greater than 4G		
<b>Operating Power</b>			
DC10.5V ~ DC18V (50VA) (optional) AC24V (60VA)			

Global CCTV Security Co.,Ltd

[ztcmobile@hotmail.com](mailto:ztcmobile@hotmail.com)

visit us : <http://www.globalcctvsec.com>

